

HYDROBURN®

Diesel Fuel Treatment

FOR USE WITH UNDERGROUND & ABOVE
GROUND TANKS, ENGINES & EQUIPMENT

DIESEL, ULSD & ALL BIO-DIESEL BLENDS

This diesel fuel additive complies with the Federal Low Sulfur content requirements for use in motor vehicle and nonroad engines.



Eliminate Water in Diesel Fuel!

Water, the worst contaminate in all fuels, builds up in every fuel tank every day through condensation. Water reduces the heat of combustion which means more smoke, less power, hard starting, rough idle, poor mileage, winter freeze-ups and microbe growth. Hydroburn treatments, which are complex organic compounds, have a strong attraction to water. Hydroburn seeks out water droplets, breaks the bond between adjacent water molecules, and bonds itself to the individual molecule. The water and Hydroburn molecules become a combustible compound that liberates the water molecule as steam in the exhaust. When the fuel is agitated the combustible compounded water molecules are dispersed throughout the entire fuel tank as an emulsion. Over time the water is removed as the engine runs, "burning" it off.

- **Hydroburn®** eliminates water and water-related problems when applied correctly!! Period.
- **Hydroburn®** improves fuel quality and promotes more complete combustion, increasing MPG.
- **Hydroburn®** replaces needed lubricity and cetane lost in the ULSD refining process.

HYDROBURN fuel treatment is scientifically formulated to break the weak hydrogen bond between water molecules...and then becomes a combustible compound that liberates the water molecule as steam in the exhaust.



- **Hydroburn®** is a bio-chemical (green) fuel treatment product – water treated adequately will not freeze.
- **Hydroburn®** reduces micro-organisms by eliminating water required for respiration.

CALL NOW! 1-888-898-7187 | WWW.CIM-TEK.COM



HYDROBURN[®]

Diesel Treatment

FOR USE WITH UNDERGROUND & ABOVE
GROUND TANKS, ENGINES & EQUIPMENT

DIESEL, ULSD & ALL BIO-DIESEL BLENDS

Diesel and Heating Oil Fuel Treatment

Part No.	Description	Ctn. Wt.
60065	Hydroburn Diesel Fuel Treatment, 8 Ounce Bottles, 12 per carton	7.5#
60066	Hydroburn Diesel Fuel Treatment, 32 Ounce Bottles, 12 per carton	25#
60067	Hydroburn Diesel Fuel Treatment, 5 Gallon Pail	42#
60068	Hydroburn Diesel Fuel Treatment, 55 Gallon Drum	456#

This diesel fuel additive complies with the federal low sulfur content requirements for use in motor vehicle and nonroad engines.

Pallet Quantities

8 oz. bottles, 12 per case, 140 cases per pallet = 1680 each per pallet

32 oz. bottles, 12 per case, 60 cases per pallet = 720 per pallet

5 gallon pails = 36 per pallet

55 gallon drums = 4 per pallet

Diesel Treatment Dosing Ratio

Maintenance Dose: 1 gallon per 1000 gallons of fuel (Warm Weather). 1 gallon per 500 gallons of fuel (Cold Weather). Treat known water content 1:1. That is for each part water add one part Hydroburn. Hydroburn forms a combustible compound that liberates the water molecule as steam in the exhaust.

8 oz. bottle treats 60 gallons (30 gallons in Cold Weather)

32 oz. bottle treats 250 gallons (125 gallons in Cold Weather)

5 gallon pail treats 5,000 gallons (2,500 gallons in Cold Weather)

55 gallon drum treats 50,000 gallons (25,000 gallons in Cold Weather)

FOR USE IN ALL DIESEL FUELS, ENGINES & EQUIPMENT - ALL YEAR!

Bio-based formula upgrades fuel quality and promotes more complete combustion for reduced emissions, better mileage, easier starts, smoother idle, more power & faster acceleration.

KEEP OUT OF REACH OF CHILDREN.

HAZARDOUS, FLAMMABLE LIQUID UN 1993. Harmful or fatal if swallowed. Avoid contact with eyes or prolonged contact to skin. If swallowed call physician immediately. Avoid spillage on painted surfaces. **KEEP LID TIGHTLY CLOSED.**

CALL NOW! 1-888-898-7187 | WWW.CIM-TEK.COM

Manufactured For: Central Illinois Manufacturing Company, Bement, IL 61813

